

SPECIFICATIONS



Model	CT1025	CT2035	CT2040
Engine	Diesel	Diesel	Diesel
Gross Horsepower	26 hp	35 hp	38 hp
No. of Cylinders	3	3	3
Total Displacement	1131 cc	1826 cc	1826 cc
Fuel Tank Capacity	25.5 L	34 L	34 L
3-Point, PTO & Hydraulics			
PTO Horsepower	20.5 hp	31 hp	32.1 hp
3-Point Hitch	Category 1	Category 1	Category 1
Lift Control Type	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System
Hydraulic Lift Capacity at 24 in. Beyond Lift Point	318 kg.f	740 kg.f	740 kg.f
Rear PTO	540 rpm	540 rpm	540 rpm
Rear PTO System	Independent	Live	Live
Mid-PTO	Standard: 2200 rpm	Optional: 2000 rpm	Optional: 2000 rpm
Total Hydraulic Pump Capacity	24.6 L/min	44.4 L/min	44.4 L/min
Rear Hydraulics	Opt (2)	Std (4)	Std (4)
Lower Links	Ball	Ball	Ball
Lifting Rod	Turn-buckle	Turn-buckle	Turn-buckle
Drive System			
Transmission	HST	HST	HST
Speed Ranges	2 Range	3 Range	3 Range
Brakes	Wet Disc Type	Wet Disc Type	Wet Disc Type
Rear Differential Lock	Rear Standard	Rear Standard	Rear Standard
Four-Wheel Drive	STD-Mechanical	STD-Mechanical	STD-Mechanical
Travel Speeds (w/ Ind. Tires)			
Forward	0 - 16.6 km/h	0 - 23.9 km/h	0 - 23.9 km/h
Reverse	0 - 11.2 km/h	0 - 21.5 km/h	0 - 21.5 km/h
Dimensions			
Overall Length (with 3 pt.)	2523 mm	3070 mm	3070 mm
Overall Width (with industrial tires)	1168mm	1595 mm	1595 mm
Overall Height (with ROPS)	2226 mm	2650 mm	2650 mm
Wheelbase	1400 mm	1670 mm	1670 mm
Ground Clearance	162 mm	340 mm	340 mm
Weight	675 kg	1240 kg	1240 kg
Steering			
	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
Inside Turning Radius	2540 mm	2450 mm	2450 mm
Safety Equipment			
Safety Interlock System (neutral start-operating)	Std	Std	Std
Fold Down ROPS (roll-over protective structure)	Std	Std	Std
Fully Retractable Seatbelt	Std	Std	Std
Features			
Suspension Seat	N/A	Std	Std
Adjustable Seat	Std	Std	Std
Cup Holder	Std	Std	Std
Glow Plug Engine Pre-heat	Std	Std	Std
Toolbox	Std	Opt	Opt
Head Lights/Tail Lights	Std	Std	Std
Cruise Control	Opt	Std	Std
Horn/Hazard Flasher/Turn Signals	Std	Std	Std
Rear Working Lights	Opt	Opt	Opt
Side Mirror	Opt	Opt	Opt

*Note: Hydraulic 3 pt. lift capacity will vary depending on lift point height.