

SPECIFICATIONS



Model	CT4045	CT4055
Engine		
Gross Horsepower	45 HP	55 HP
No. of Cylinders	4	4
Total Displacement	2435 L	2435 L
Fuel Tank Capacity	48 L	48 L
3-Point, PTO & Hydraulics		
Average PTO Horsepower	38.2 HP	44 HP
3-Point Hitch	Category 1	Category 1
Lift Control Type	Hydraulic Position Control System	Hydraulic Position Control System
Hydraulic Lift Capacity	1232 kg	1232 kg
Rear PTO	540 rpm	540 rpm
Rear PTO System	Independent	Independent
Mid-PTO	N/A	N/A
Total Hydraulic Pump Capacity	62.4 L/min.	62.4 L/min.
Rear Hydraulics	Standard (1set)	Standard (1set)
Lower Links	Ball	Ball
Lifting Rod	Turnbuckle	Turnbuckle
Drive System		
Transmission	HST	HST
Speed Ranges	Infinite, 3 Ranges	Infinite, 3 Ranges
Brakes	Wet Disc Type	Wet Disc Type
Rear Differential Lock	Rear Standard	Rear Standard
Four-Wheel Drive	Standard	Standard
Travel Speeds (w/ Ind. Tires)		
Forward	0 - 29.7 km/h	0 - 29.7 km/h
Reverse	0 - 20.8 km/h	0 - 20.8 km/h
Dimensions		
Overall Length (w/ 3 pt.)	3189 mm	3189 mm
Overall Width (w/ industrial tires)	1730 mm	1730 mm
Overall Height (w/ ROPS)	2270 mm	2270 mm
Wheelbase	1810 mm	1810 mm
Ground Clearance	368 mm	368 mm
Weight	1596 kg	1596 kg
Steering		
Inside Turning Radius	2610 mm	2610 mm
Tilt Steering Wheel	Standard	Standard
Safety Equipment		
Fold Down ROPS (roll-over protective structure)	Std	Std
Fully Retractable Seatbelt	Std	Std
Features		
Fully Adjustable Premium Seat	Std	Std
Linked Pedal	Std	Std
Rubber Floor Mat	Std	Std
Manual/ Auto PTO Switch	Std	Std
Cup Holder	Std	Std
Glow Plug Engine Pre-heat	Std	Std
Toolbox	Std	Std
Head Lights/Tail Lights/ Brake Lights	Std	Std
Cruise Control	Std	Std
Horn/Hazard Flasher/Turn Signals	Std	Std
Side Mirror	Std (LH1)	Std (LH1)

*Note: Hydraulic 3 pt. lift capacity will vary depending on lift point height.