

## Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	55.2 kW
Turbocharged Engine	×
Engine Model	D24 BSH T4 74 HP DM02- LEL00 Bobcat V2
Engine Make	Bobcat
Displacement	2,401 cm <sup>3</sup>
Torque RPM	1,800 rpm
Number of Cylinders	4

## Performance

Rated Operating Capacity (ISO)	1111 kg
Operating Capacity (50% of Tip)	1588 kg
Rated Operating Capacity (35% Of Tip)	1111 kg
Tipping Load	3175 kg
Operating Weight	4049 kg
Travel Speed	11.6 km/ h
Travel Speed (2- speed option)	16.4 km/ h
Ground Pressure (Rubber)	0.41 bar

## Capacities

Fuel Tank	107.1 l
-----------	---------

## Hydraulic System

System Relief @ Quick Couplers	241.32 bar
Auxiliary Std Flow	66.6 l/ min
Auxiliary High Flow	101.8 l/ min

## General

Contract Codes	Compact Track Loader
First Year of Production	2020

## Controls

Hydraulic (Lift and Tilt)	Dual Levers
Control Option	Selectable Joystick Controls
Auxiliary Hydraulics Type	Finger Tip Control

## Dimension

Length	3426 mm
Length without Attachment	2718 mm
Length with Standard Bucket	3426 mm
Width	1702 mm
Width (with bucket)	1727 mm
Height	2045 mm
Height with Operator Cab	2045 mm
Height to Bucket Hinge Pin	3048 mm
Reach @ Maximum Height	932 mm
Turning Radius	2070 mm
Length of track on ground	1379 mm
Track Width	320 mm
Track Width - Optional	399 mm
Ground Clearance	190.5 mm
Standard Tracks	320 mm
Dump Angle @ Maximum Height	37°

## Features

Joystick Control	×
Air Conditioning	×
Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	×
Operating Lights	■
Suspension Seat	■
Two Speed Travel	×
Deluxe Instrumentation	×
Engine Shutdown	■
Hydraulic Bucket Positioning	×
High Flow Option	×
Auxiliary Hydraulics	■
Bob- Tach Attachment System *	■
Power Bob- Tach *	×
ACS (Switchable Controls)	□
Ride Control	×
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.