

Configuration	Standard	Roller Suspension Option
---------------	----------	--------------------------

## Engine

Emissions Tier (EPA)		Tier 4
Engine Cooling		Liquid
Engine Fuel		Diesel
Horsepower		68.6 kW
Turbocharged Engine		×
Engine Model		3.4L Bobcat Engine
Engine Make		Bobcat
Displacement		3,409 cm <sup>3</sup>
Torque RPM		1,600 rpm
Number of Cylinders		4

## Performance

Rated Operating Capacity (ISO)		1576 kg
Operating Capacity (50% of Tip)		2250 kg
Rated Operating Capacity (35% Of Tip)		1576 kg
Tipping Load		4504 kg
Operating Weight		4770 kg
Travel Speed		10.6 km/ h
Travel Speed (2- speed option)		17.2 km/ h
Ground Pressure (Rubber)		0.29 bar

## Capacities

Fuel Tank		165.8 l
-----------	--	---------

## Hydraulic System

System Relief @ Quick Couplers		241.32 bar
Auxiliary Std Flow		87.1 l/ min
Auxiliary High Flow		138.5 l/ min

## General

Contract Codes		Compact Track Loader
----------------	--	----------------------

## Controls

Hydraulic (Lift and Tilt)		Dual Pedals
Control Option		Selectable Joystick Control (SJC)
Auxiliary Hydraulics Type		Fingertip Control

## Dimension

Length		3597 mm
Length without Attachment		2903 mm
Length with Standard Bucket		3597 mm
Width		1981 mm
Width (with bucket)		2032 mm
Height		2065 mm
Height with Operator Cab		2065 mm
Height to Bucket Hinge Pin		3338 mm
Reach @ Maximum Height		894 mm
Turning Radius		2235 mm
Length of track on ground		1618 mm
Track Width		450 mm
Ground Clearance		238.76 mm
Dump Angle @ Maximum Height		37°

## Features

Joystick Control	×
Air Conditioning	×
Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	×
Operating Lights	■
Suspension Seat	■
Two Speed Travel	×
Deluxe Instrumentation	×
Engine Shutdown	■
Hydraulic Bucket Positioning	×
High Flow Option	×
Auxiliary Hydraulics	■
Bob- Tach Attachment System *	■
Power Bob- Tach *	×
ACS (Switchable Controls)	×
Ride Control	×
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.